

## 双闸板平板闸阀



主要外形尺寸 ( mm ) Main External and Connection Dimension

型号 type	DN	L	D	D1	D2	b	Z-Φd	H	Do
Z44WF/WY-16C KZ44WF/WY-16C	25	127	115	85	65	14	4-Φ14	280	200
	32	140	135	100	76	16	4-Φ18	322	200
	40	165	145	110	85	16	4-Φ18	380	250
	50	250	160	125	100	16	4-Φ18	415	250
	65	280	180	145	120	18	4-Φ18	470	300
	80	310	195	160	135	20	4-Φ18	540	300
Z544WF/WY-16C KZ544WF/WY-16C	100	350	215	180	155	20	4-Φ18	605	350
	125	385	245	210	185	22	8-Φ18	785	350
Z44WF/WY-16C KZ44WF/WY-16C	150	450	280	240	210	24	8-Φ23	925	350
	200	550	335	295	265	26	12-Φ23	1125	350
Z944WF/WY-16C KZ944WF/WY-16C	250	650	405	355	320	30	12-Φ25	1350	450
	300	750	460	410	375	30	12-Φ25	1485	500
	350	850	520	470	435	34	16-Φ25	1705	550
	400	950	580	525	485	36	16-Φ30	1870	600
	450	1050	640	585	545	40	20-Φ30	2185	800
	500	1150	705	650	608	44	20-Φ34	2335	800
600	1350	840	770	718	48	20-Φ41	2680	1000	



# 双闸板平板闸阀

**主要外形尺寸 ( mm ) Main External and Connection Dimension**

型号 type	DN	L	D	D1	D2	b	Z-Φd	H	Do
Z44WF/WY-25 KZ44WF/WY-25	25	127	115	85	65	16	4-Φ14	280	200
	32	140	135	100	78	18	4-Φ18	322	200
	40	165	145	110	85	18	4-Φ18	380	250
	50	250	160	125	100	20	4-Φ18	415	250
	65	280	180	145	120	22	8-Φ18	470	300
Z544WF/WY-25 KZ544WF/WY-25	80	310	195	160	135	22	8-Φ18	540	300
	100	350	230	190	160	24	8-Φ23	605	350
	125	385	270	220	188	28	8-Φ25	785	350
Z44WF/WY-25 KZ44WF/WY-25	150	450	300	250	218	30	8-Φ25	925	350
	200	550	360	310	278	34	12-Φ25	1125	350
Z944WF/WY-25 KZ944WF/WY-25	250	650	425	370	332	36	12-Φ30	1350	450
	300	750	485	430	390	40	16-Φ30	1485	500
	350	850	550	490	448	44	16-Φ34	1705	550
	400	950	610	550	505	48	16-Φ34	1870	600
	450	1050	660	600	555	50	20-Φ34	2185	800
	500	1150	730	660	610	52	20-Φ41	2335	800
	600	1350	840	770	718	56	20-Φ41	2680	1000

**主要外形尺寸 ( mm ) Main External and Connection Dimension**

型号 type	DN	L	D	D1	D2	b	Z-Φd	H	Do
Z44WF/WY-40 KZ44WF/WY-40	25	127	115	85	65	16	4-Φ14	280	200
	32	140	135	100	78	18	4-Φ18	322	200
	40	165	145	110	85	18	4-Φ18	380	250
	50	250	160	125	100	20	4-Φ18	415	250
	65	280	180	145	120	22	8-Φ18	470	300
Z544WF/WY-40 KZ544WF/WY-40	80	310	195	160	135	22	8-Φ18	540	300
	100	350	230	190	160	24	8-Φ23	605	350
	125	385	270	220	188	28	8-Φ25	785	350
Z44WF/WY-40 KZ44WF/WY-40	150	450	300	250	218	30	8-Φ25	925	350
	200	550	375	320	282	38	12-Φ30	1125	350
Z944WF/WY-40 KZ944WF/WY-40	250	650	445	385	345	42	12-Φ34	1350	450
	300	750	510	450	408	46	16-Φ34	1485	500
	350	850	570	510	465	52	16-Φ34	1705	550
	400	950	655	585	535	58	16-Φ41	1870	600
	450	1050	680	610	560	60	20-Φ41	2185	800
	500	1150	755	670	612	62	20-Φ48	2335	800
	600	1350	890	795	730	62	20-Φ54	2680	1000